

ALL-AROUND RACK PRESS

Ø® dich





Item No.: VH-26.00182

Main features:

Ø runner: 24 mm Bed gap: 55 mm Max.distance plate-runner: 95 mm Ø plate: 80 mm

Ground surface : 115 x 185 mm Total height (min/max): 250 / 330 mm Runner boring: Ø 10 mm Plate boring: Ø 12 mm Weight: 7 kg

Type: Universal press particularly adapted for assembling works, glass or back driving operation. Suitable for production units as well as for after sales services. Steadiness, versatility and pressure strength are the main assets of this equipment.

Making: A robust construction with a frame in first quality grey cast-iron. Lever 360° positionable and swivelling thanks to lateral pulling (Jaccard system). The spindle catch can be positioned on the whole running length, fine setting with a screw stop. The lever can be assembled on the right or the left. (The press is originally delivered with the lever on the right side).

Fixing: With a M8 internal screw thread underneath the press to fix it on the working bench or on a board with screws or bolts

Delivery: Ready for use, delivered with 2 Allen keys and 1 pin/adjusting nut 1.

Accessories (options):

VH-26.00161: Reducing bush Ø 12.0 mm / 10.0 mm

VH-26.00035: Set of M6 joining pieces (for standard stakes)

香港九龍荔枝角長順街 19 號楊耀松(第六)工業大廈 10 樓 A1 室

Flat A1, 10/F., Yeung Yiu Chung 6th Ind. Bldg., 19 Cheung Shun Street, Lai Chi Kok, Kowloon, Hong Kong.
Tel: (852) 2664 9999 Fax: (852) 2512 6491 Email: info@jcucl.com Website: www.jcucl.com