




Cyclomotion Watch Winder



Cyclomotion winding machine with protect cover, clips for 12 wristlet watches, 1 / 4 rpm, 110-240V



EL-1035170/PRO12

=

EL-1035170

6x EL-1035190



Cyclomotion winding machine with protect cover, clips for 24 wristlet watches, 1 / 4 rpm, 110-240V



EL-1035170/PRO24

=

EL-1035170

6x EL-1035192



Cyclomotion winding machine without protect cover, clips for 12 wristlet watches, 1 / 4 rpm, 110-240V



EL-1035171/12

=

EL-1035171

6x EL-1035190



Cyclomotion winding machine without protect cover, clips for 24 wristlet watches, 1 / 4 rpm, 110-240V



EL-1035171/24

=

EL-1035171

6x EL-1035192



Watch Clip

Watch Clip

Industrial clip

Watch box

for 2 watches
with straps

for 4 watches
with straps

for 4 watches
without straps

for 4 watches
without straps

Max. watch length	165 – 205mm	165 – 205 mm	-	-
Max. watch dia.	-	-	-	43mm
Max. load/ watch holder	180g	180g	180g	180g
	EL-1035359	EL-1035360	EL-1035361	EL-1053528

The professional watch winder

The Cyclomotion with a modern design is the perfect further development of the proven Cyclomat for winding mechanical watches. The various possible options for watch mounting enable individual configuration of the watch winder tailored to the respective requirements. Different winding variants guarantee optimum winding and testing according to the respective requirements of the watch movements. In particular, large and heavy mechanical watches can also be wound by the powerful motor. Due to its versatility, the Cyclomotion is designed for watch manufacturers and watchmakers

Product Features

- powerful, quiet motor with integrated slip clutch and holding torque (in standby mode)
- adjustable speed: 1 rpm or 4 rpm for continuous tests and fast winding of the watches
- adjustable rotation directions: clockwise, anti-clockwise and clockwise / anticlockwise by rotation direction change
- individually selectable retaining bracket combination enables simultaneous winding on one or both sides of watch movements to be wound
- Cyclomotion pro with lockable protection cover provides additional protection against dust and mechanical influence

Technical data

Rotational direction	Left / Right	Weight Cyclomotion pro (kg)	Approx. 16
Rotation radial (rpm)	1 or 4	Clip (kg/pce)	Approx. 0.1
Rotation axial (rpm)	4.5 or 18	Mains voltage (VAC)	100 – 240
Cyclomotion max. (mm)	W465 x D325 x H520	Mains frequency (Hz)	50 / 60
Cyclomotion pro max. (mm)	W635 x D325 x H585	Power consumption total (W)	Approx. 24
Weight Cyclomotion (kg)	Approx. 11	Power consumption total standby (W)	Approx. 24